

I claim:

- 3 1. A cannula system, comprising:
  - a pair of extension tubes;
  - a divided cannula coupled between said pair of extension tubes;
  - 6 a pair of earpieces for cooperating with said pair of extension tubes to support said divided cannula in a desired position relative to the nostrils of a patient;
  - 9 each individual one of said pair of earpieces including:
    - a front eye hole for guiding an individual one of said pair of extension tubes into a recessed channel disposed on a top portion of the
    - 12 individual earpiece; and
    - a rear eye hole for helping to secure said individual one of said pair of extension tubes into a desired position within said recessed
    - 15 channel.
- 18 2. A cannula assembly, comprising:
  - slider tube extension means for helping to facilitate a distance adjustment;
  - nasal cannula means coupled between said slider tube extension means
  - 21 for facilitating both the delivery of and collection of gases;
  - ramped ear piece means coupled to said nasal cannula means by said slider tube extension means for facilitating supporting said nasal
  - 24 cannula means from the ears of a user; and
  - said ramped ear piece means including open recessed channel means disposed between bridge means for helping to facilitate user
  - 27 adjustment of the distance between said nasal cannula means and said ear piece means.
- 30 3. The cannula assembly according to claim 2, wherein said ear piece means further includes means defining a tube locking hole for helping to secure said nasal cannula means in a fixed position relative to said ear piece means.

4. The cannula assembly according to claim 3, wherein said ear piece means  
3 further includes stop means for helping to limit an adjustment distance  
between said nasal cannula means and said ear piece means.

6 5. The cannula assembly according to claim 4, wherein said nasal cannula  
means is a divided oxygen/carbon dioxide nasal cannula having a pair of  
spaced apart nasal tips of sufficient length for insertion into the nostrils of the  
9 user.

6. The cannula assembly according to claim 5, wherein said pair of spaced  
12 apart nasal tips have substantially smaller outer diameter than said nasal  
delivery tube.

15 7. The cannula assembly according to claim 6, wherein said pair of spaced  
apart nasal tips are trimmable to custom fit the user.

18 8. The cannula assembly according to claim 7, wherein said slider tube  
extension means includes a pair of extension tubes each having a given  
diameter.

21 9. The cannula assembly according to claim 8, wherein said ear piece means  
includes a pair of ear pieces; and  
24 wherein each individual one of said pair of ear pieces has disposed thereon an  
open recessed channel for helping to facilitate supporting therein at least a  
portion of an individual one of said pair of extension tubes.

27 10. The cannula assembly according to claim 8, wherein stop means is coupled  
to a proximal end of said ear piece means and includes means defining a tube  
30 entrance hole for helping to facilitate guiding an individual one of said pair of  
extension tubes into a corresponding one of said open recessed channel and to

facilitate securing slidably an individual one of said pair of extension tubes to said ear piece.

3

11. The cannula assembly according to claim 10, further comprising:  
a securing clip mounted to said section of fluid delivery tubing to help secure  
6 the fluid delivery tubing in a fixed position relative to the user.

12. The cannula assembly according to claim 11, further comprising:  
9 a securing clip mounted to the other one of said pair of extension tubes to help  
secure the other one of said pair of extension tubes in a fixed position relative  
to the user.

12

13. A cannula system, comprising:  
a nasal cannula coupled to a pair of extension tubes;  
15 a pair of earpieces for supporting and retaining said extension tubes  
and said nasal cannula in a fixed position; and  
wherein each individual earpiece includes a pair of guides with a  
18 recessed channel disposed therebetween for receiving and retaining therein an  
individual one of the extension tubes.

21 14. The cannula system according to claim 13, wherein said nasal cannula is a  
divided nasal cannula for facilitating the delivery of and collection of gases.

24 15. The cannula system according to claim 13, wherein one of said pair of  
guides is an exit bridge disposed adjacent to an exit hole, said exit bridge  
having a hole extending therethrough for providing access to said exit hole to  
27 provide an extension tube exit path from said recessed channel to said exit  
hole.

30 16. The cannula system according to claim 15, wherein said recessed channel  
terminates in an inclined ramp disposed at about said oval shaped exit hole.

17. The cannula system according to claim 16, wherein said exit hole is oval shape having its long axis extending along the longitudinal axis of said  
3 earpiece.

18. The cannula system according to claim 17, wherein said inclined ramp  
6 reaches it apex at the distal end of the long axis of said oval said exit hole to provide an exit path that cause the extension tube to be wedged into engagement with said exit bridge.

9  
19. The cannula system according to claim 18, wherein the other one of said bridges is an entrance bridge, said entrance bridge having an entrance hole  
12 extending therethrough for providing access to said recessed channel to provide an extension tube entrance path from said nasal cannula to said recessed channel; and  
15 wherein said entrance bridge, said inclined ramp and said exit bridge cooperate to facilitate capturing the extension tube in a fixed position to secure said cannula at a desired position relative to the nostrils of a patient.

18  
20. The cannula system according to claim 19, wherein said nasal cannula has a single tube with at least one gas outlet channel and with at least gas inlet  
21 channel for facilitating both the delivery of and the collection of gases;  
said single tube having a given diameter and being disposed between a pair of slider extension tubes, wherein each slider extension tube has another  
24 given diameter substantially smaller than said given diameter; and  
wherein each ear piece has a tube entrance hole with a  
sufficient diameter for receiving therethrough one of said pair of slider  
27 extension tubes but not a sufficient diameter for receiving therethrough said single tube for helping to limit an adjustment distance between the nasal cannula and individual ones of said pair of ear pieces.

30